



**CO METER**

**Model : GCO-2008**

- \* CO ( Carbon monoxide ), Temperature.
- \* CO range : 0 to 1,000 ppm.
- \* Temperature : 0 to 50 °C, °C/°F.
- \* CO response time : 30 second.
- \* Data hold Record ( Max., Min. ), RS232
- \* 1.5 V battery ( UM-4/AAA ) x 6 PCs or DC 9V adapter in.



**STROBOSCOPE**

*digital synthesis, high intensity light*

**Model : DT-2349**

- \* Digital synthesis circuit, high stability and easy adjustment.
- \* Range : 60 to 32,000 RPM.
- \* Adjustment resolution : 0.1 RPM/1 RPM.
- \* High intensity light.
- \* DCV power supply via external AC/DC adapter or can be used the optional recharge batteries.
- \* Setting button : digital rotate button, X 2 button, ÷ 2 button, + button, - button, easy to adjust the desired RPM.



**CHLORINE METER**

**Model : CL-2006**

- \* Free chlorine, total Chlorine measurement.
- \* Range : 0 to 10 ppm.
- \* Range : Auto range.
- \* Measuring principal : Photo meter method.
- \* Light source : LED, 650 nm.
- \* Record Max, Min. value.
- \* Power : 1.5 V battery ( UM-4/AAA ) x 6 PCs.



**UV LIGHT METER**

**Model : YK-35UV**

- \* Spectrum : 290 nm to 390 nm
- \* UVA & UVB measurement.
- \* Calibration is under UVA.
- \* 2 ranges :  
2 mW/cm<sup>2</sup> x 0.001 mW/cm<sup>2</sup>.  
20 mW/cm<sup>2</sup> x 0.01 mW/cm<sup>2</sup>.
- \* Data hold, Record ( Max., Min. ), RS232.



**BENCH**

**PH/ORP, DO, CD/TDS METER**

**Model : WA-2015**

- \* Bench meter for multi purpose operation : PH/ORP, DO, CD/TDS Measurement.
- \* pH : 0 to 14.00 pH, ORP : 1999 mV.
- \* Conductivity : 200 uS/2 mS/20 mS/200 mS.
- \* Dissolved oxygen : 0 to 20.0 mg/L.
- \* ATC ( automatic temperature compensation ).
- \* Real time 16,000 no. data logger.
- \* Data hold, Record ( Max., Min. ), RS232
- \* Optional electrode : pH, ORP, CD, DO ATC electrode, ACT probe.
- \* DC 1.5V ( UM-3, AA ) x 4 or DC 9V adapter in.



**3 PHASE POWER ANALYZER**

**Model : DW-6092**

- \* 3 phase/4 wire, 3 phase/3 wire, 1 phase/2 wire, 1 phase/3 wire
- \* True rms measurement for ACA, ACV.
- \* True power : W, KW, MW.
- \* VA, KVA, MVA, VAR, KVAR, MVAR.
- \* PF ( power factor ), phase angle.
- \* WH, KWH, KVARH, PFH.
- \* ACA : 0.1 A to 2,000 A.
- \* 17,000 data logger.
- \* Harmonic measurement ( 1 to 50th ).
- \* Display all measuring electrical wave shape.



**ELECTRODE HOLDER**

**Model : EH-20**

- \* Electrode holder for all LUTRON pH electrode and the ATC temperature probe.