



POWER SUPPLY MODULES

Suitable for supplying fixed and variable alternating current and fixed and variable rectified direct current, in order to easily carry out all the tests on electrical machines of the UNILAB laboratory and in general in an electric measurement laboratory. Provided with start push-button with remote control switch, stop push-button, key-unlocked emergency mushroom head pushbutton and differential magneto-thermal protection on the main sockets. Connector for the overspeed protection of the motors. The control devices and the safety connecting terminals, according to the IEC standards, are arranged on the front.

DL 1013M2

Output voltages:

Variable ac 3x0-430 V, 5 A / 3x0-240 V, 8 A
Fixed ac 3x380 V + N, 16 A / 3x220 V, 8 A
Standard fixed ac 220 V, 10 A
Variable dc 0-240 V, 10 A / 0-225 V, 1 A
Fixed dc 220 V, 10 A

Power supply 3x380 V + N, 50/60 Hz

DL 1013M3

Output voltages:

Variable ac 3x0-440 V, 4.5 A / 3x0-240 V, 8 A
Fixed ac 3x380 V, 4.5 A / 3x220 V + N, 16 A
Standard fixed ac 127 or 220 V, 10 A
Variable dc 0-240 V, 10 A / 0-225 V, 1 A
Fixed dc 220 V, 10 A

Power supply 3x220 V + N, 50/60 Hz



DL 1013M1

Output voltages:

Variable ac 3x0-440 V, 5 A (programmable)
3x0-240 V, 10 A (programmable)
Fixed ac 3x380 V + N, 16 A
Standard fixed ac 220 V, 10 A
Variable dc 0-290 V, 12 A (programmable)
0-225 V, 1 A
Fixed dc 220 V, 10 A

Power supply 3x380 V + N, 50/60 Hz