



MOVING IRON VOLTMETER



DL 2109T3PV

Moving iron meter for ac and dc voltage measurements.

Technical features:

Scale: 50 divisions
Range: 125-250-500 V
Range changeover switch.
Accuracy class: 1.5

POWER METER



DL 2109T26

Demonstration single-phase meter for active power and capacitive/inductive reactive power.

Technical features:

Measurement ranges:
Voltage: 3/10/30/100/300/1000V
Current: 0.1/0.3/1/3/10/30 A
Frequency range: 0 ... 20 kHz
Active power: 0 ... 20 W
Reactive power: 50 Hz
LED indicators: capacitive reactive power, inductive reactive power, overload voltage (with acoustic signal), overload current (with acoustic signal).
Auxiliary supply: single-phase from mains

TRUE RMS METER



DL 2109T33

Demonstration meter for measuring the true rms of voltages and currents.

Technical features:

Voltage: 3/10/30/100/300/1000 V (input resistance 10 MW)
Current: 0.1/0.3/1/3/10/30 A
Continuous overload protection in all ranges.
Auxiliary supply: single-phase from mains

MOVING IRON AMMETER



DL 2109T2A5

Moving iron meter for ac and dc current measurements.

Technical features:

Scale: 50 divisions
Range: 2.5 A