ACA LEAKAGE TESTER

Model: DL-6054 *ISO-9001, CE, IEC1010*







The Art of Measurement

ACA LEAKAGE TESTER

Model: DL-6054

FEATURES

- * High precision AC mA measurement, it is useful for AC mA leakage current measurement.
- * Measure AC mA on the inductive conductor.
- * Miniature type, easy to carry out & operation.
- * High precision for low ACA leakage current measurement.
- * Built-in DATA HOLD function.
- * Crystal time base, high quality.
- * LCD display allows clear readout-out even at high ambient light level.
- * LSI circuit provides high reliability and durability.
- * Overload protection circuit is provided for all range.
- * Design to meet IEC 1010 safety requirement.
- * Compact, light weight and excellent operation.

| SPECIFICATIONS | |
|--------------------|--|
| Display | 13 mm (0.5") LCD, 3 1/2 digits. |
| | Max. indication 1999. |
| Measurement & | 200 AC mA x 0.1 mA |
| Resolution | 20 ACA x 0.01 A |
| | 200 ACA x 0.1 A |
| Data Hold | Available to hold the measuring values |
| | on the display. |
| Accuracy | ± (1.2 % + 5 d) |
| (23 5 蚓) | * Specification be tested on sine wave 50, 60 Hz. |
| Time Base | Quartz crystal, 32768 Hz. |
| Overload Circuit | 300 ACA max. (within 1 minute for 20A, |
| Protection | 200A range). |
| Zero adjustment | Automatic adjustment. |
| Over input | Display shows '1'. |
| Sampling Time | Approx. 0.4 second. |
| Operating Temp. | 0 to 50 $^{\circ}\mathrm{C}$ (32 to 122 $^{\circ}\mathrm{F}$). |
| Operating Humidity | Less than 80% RH. |
| Battery | 006P DC 9V battery. |
| Power Consumption | Approx. DC 1.2 mA. |
| Weight | 200 g/0.44 LB (including battery). |
| Dimension | HWD 180 x 47 x 35 mm. |
| | 7.1 x 1.9 x 1.4 inch. |
| Conductor Size | 19 mm Dia. |
| Accessories | Operation manual 1 PC. |
| Included | Carrying case |

^{*} Appearance and specifications listed in this brochure are subject to change without notice.