

SUGGESTED CONFIGURATIONS

	DL 2102AL	DL 2101T13	DL 2102T01	DL 2102T02	DL 2102T03	DL 2102T04	DL 2102T67	DL 2102T05	DL 10115AV	DL 2102T09	DL 2102A	DL 2102D	DL 2109T04	DL 2102T12	JL 2102T15	JL 2102T24	DL 2102T25	JL 2102T26	DL 2102T11	JL 2102T16	DL 2102T17	DL 2102T18	DL 2102T19	DL 2102T20	DL 2102T20RMB	DL 2102T30RM86	DL 2102T31V	DL 2102T38	DL 2102ALCC	DL 2100-3M	rl 2102T
DL 2102TA																															
Single-pole control	1	1	1		1																									1	1
auxiliaries Contactor	1	1		1	1	1																								1	H
Logic operators	1	1		1	1	1																								1	1
Contactor self-supply	1	1		1	1	1																								1	1
Interlock between	1	1		1	1	2																								1	1
contactors																															
Sequentially controlled contactors	1	1		1	1	2																								1	1
Exclusive-OR operator	1	1		1	1	2																								1	1
Excitation delayed timer	1	1	<u> </u>	1	1	1	1					<u> </u>		1								<u> </u>		<u> </u>					1	1	1
De-excitation delayed timer	1	1		1	1		1																							1	1
Static timer	1	1		1	1	1	1															\vdash		\vdash						1	1
DL 2102TB	Ĺ	Ī		Ĺ	Ī	Ĺ	Ī																							Ĺ	Ī
Thermal relay	1	1		1	1	1		1	1																					1	1
Manual star/delta starting	1	1		1	1	3			1																					1	1
Manual reverser	1	1		1	1	2			1																					1	1
Timed sequence control	1	1		1	1	2	2																							1	1
Pulse generator	1	1		1	1	2	2																							1	1
Automatic star/delta starting	1	1		1	1	3	1	1	1																					1	1
Star/delta starter with reverser	1	1		1	1	4	1	1	1																					1	1
Counter-current braking	1	1		1	1	4	1		1																					1	1
DL 2102TC																															
Manual starter with rotor resistances	1	1	1	1	1	3		1		1	1																			1	1
Automatic starter with	1	1	1	1	1	3	2	1		1	1																			1	1
rotor resistances Speed variator for	1	1		1	1	3		1				1																		1	1
Speed variator and	1	1		2	2	5		1				1																		1	1
reverser for Dahlander motor																															
Automatic reverser for three-phase	1	1		1	1	4	1		1																					1	1
asynchronous motor DL 2102TD																															
Motor starting with switch	1								1				1																	1	1
Star/delta starting with switch	1								1					1																1	1
Reverser with switch	1								1		H				1				H		H									1	1
Star/delta starting, 2 rotation directions, with switch	1								1							1														1	1
Speed variator for Dahlander motor with switch	1											1					1													1	1
Speed variator for Dahlander motor, 2 rotation directions, with switch	1											1						1												1	1



ELECTRICAL INDUSTRIAL INSTALLATIONS



DL 2102TE																												1	DΕ		RE
Motor starting and control with limit switch	1	1		1	1	1		1	1										1											1	1
Motor starting and control with inductive sensor	1	1		1	1	1		1	1											1									1	1	1
Motor starting and control with capacitive sensor	1	1		1	1	1		1	1												1								1	1	1
Motor starting and control with photoelectric barrage sensor	1	1		1	1	1		1	1													1							1	1	1
Motor starting and control with photoelectric reflecting sensor	1	1		1	1	1		1	1														1						1	1	1
Motor starting and control with level sensor	1	1		1	1	1		1	1															1					1	1	1
Motor starting and control with level variations	1	1		1	1	1		1	1																1	1				1	1
Motor starting and control with pulse programmer	1	1		1	1	1		1	1														1				1		1	1	1
Sequence of motor starting, 2 rotation directions, with motor stop between the 2 operations with cam programmer	1	1		1	1	4		1	1																			1		1	1
Total	1	1	1	2	2	5	2	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	2	1