## psi, KPa, in-Hg, cm-Hg, DC mV output **PRESSURE ADAPTER** Model : PS-403 ISO-9001, CE, IEC1010







The Art of Measurement

## **PRESSURE/VACUUM ADAPTER**

Model : PS-403

|   | S  | PECIF  | ICATIONS                      |  |
|---|--|--|-------------------------------|--|
| Range                                   | Pressure   | psi  | 0.5 to 500 psi                |  |
|   |  | kPa  | 3.447 to 3447 kPa             |  |
|   | Vacuum   | in-Hg  | 0 to 29.99 in-Hg              |  |
|   |  | cm-Ĥg  | 0 to 76 cm-Hg                 |  |
| Accuracy                                | kPa  | 3.5 to 1724 kPa : ± (1 % + 3.5 kPa)  |                               |  |
| * After Calibration<br>* Temp. 23± 5 °C |  | 1725 to 2413 kPa : ± (2 % + 3.5 kPa)<br>2414 to 3447 kPa : ± (5 % + 3.5 kPa) |                               |  |
|   | psi  | 2.11110001171111111111111111111111111111                                     |                               |  |
|   | ,  | 251 to 350 psi : ± (2 % + 0.5 psi)   |                               |  |
|   |  | 351 to 500 psi : ± (5 % + 0.5 psi)   |                               |  |
|   | cm-Hg  | $0.76 \text{ cm-Hg}$ : $\pm (5\% + 1.3 \text{ cm-Hg})$                       |                               |  |
|   | in-Hg  |  | 99 in-Hg :± (1 % + 0.5 in-Hg) |  |
| Output                                  | kPa<br>,   | 1 kPa/1 mV   |                               |  |
| Signal                                  | psi  | 1 psi/1 mV   |                               |  |
|   | cm-Hg  | 1 cm-Hg/1 mV   |                               |  |
|   | <i>in-Hg</i> 1 in-Hg/1 mV  |  |                               |  |
| Zero adjust.                            | Adjust Potentiometer on the front panel.                                 |  |                               |  |
| Pressure                                | 1/4" PS  |  |                               |  |
| Port Connector                          |  |  |                               |  |
| Meter input                             | 10 Meg ohm (If the meter input impedance is 1 Meg ohm, then ad 0.5%      |  |                               |  |
| Impedance                               | to basic accuracy specification.)  |  |                               |  |
| Max. working Pressure                   | 500 psi  |  |                               |  |
| Temperature Coefficient                 | 1% Span (0   | ) to 50 °(   | C)/max.                       |  |
| of Span                                 |  |  |                               |  |
| Operating                               | Temperature  |  | umidity                       |  |
| Temperature/<br>Humidity                | -10 to 10 ℃  | 0 to   | 90% R.H.                      |  |
|   | <b>11 to 30</b> °C   | ,  |                               |  |
|   | <b>31 to 40</b> °C   | 0 to   | 75% R.H.                      |  |
|   | <b>41 to 50</b> ℃  | 0 to   | 45% R.H.                      |  |
| Measured                                | The Pressue/Vacuum Adapter is compatible with industrial gases and       |  |                               |  |
| Materials                               | liquids that are compatible with 316 stainless steel. To determine the   |  |                               |  |
| Compatibility                           | compatibility of a liquid or gas, refer to manufacture's specifications. |  |                               |  |
|   | When making measurements, be make sure that liquids or gases in those    |  |                               |  |
|   | systems are compatible. If they are not, contamination or damage to the  |  |                               |  |
|   | Pressure Adapter may result.   |  |                               |  |
| Battery                                 | Standard 9V battery (006P, 6F22 or NEDA ± 1604), heavy duty type.        |  |                               |  |
| Power Consumption                       | Approx. DC 1.2 mA.   |  |                               |  |
| Weight                                  | 285 g/0.63 LB - included pressure sensor.                                |  |                               |  |
| Size                                    |  | Main instrument : 10 x 5 x 2.5 cm  |                               |  |
|   | Pressure Sensor : 55 mm x 30 mm Dia.                                     |  |                               |  |
| Cable Length                            | Approx. 1 meter/3.3 feet.  |  |                               |  |
| Accessories                             | Operation manual 1 PC  |  |                               |  |
| Included                                | 500 psi pressure transducer 1 PC   |  |                               |  |

\* Appearance and specifications listed in this brochure are subject to change without notice.

0604-PS403